



CIRCUIT-BREAKER VL 1250N STANDARD
 BREAKING CAPACITY ICU=55KA / 415 V AC 3 POLE,
 LINE PROTECTION ELECTRONIC TRIP UNIT ETU22,
 LSIG 3PHASES/3WIRES IN=1250A, RATED
 CURRENT IR=500-1250A, OVERLOAD
 ISD=1,5TO9XIR, II=10XIN SHORT-CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		ETU22
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL7
Electrical endurance (switching cycles) / typical		1 500
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		3 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	30
Voltage		
Rated operational voltage Ue / max.	V	690
Insulation voltage		
• rated value	V	800
• at AC / rated value	V	800

Surge voltage resistance / rated value	kV	8
--	----	---

Protection class

Protection class IP		IP20
Protective function of the overcurrent release		LSIG

Electricity

Continuous current / rated value	A	1 250
Derating temperature / for the rated value of the continuous current	°C	50
Adjustable pick-up value current		
<ul style="list-style-type: none"> of the current-dependent overload release / Full-scale value 	A	1 250
<ul style="list-style-type: none"> of instantaneous short-circuit trip unit / initial value 	A	12 500
<ul style="list-style-type: none"> of instantaneous short-circuit trip unit / Full-scale value 	A	12 500

Main circuit

Operating frequency		
<ul style="list-style-type: none"> 1 / rated value 	Hz	50
<ul style="list-style-type: none"> 2 / rated value 	Hz	60
Operating voltage		
<ul style="list-style-type: none"> for main current circuit / at AC / at 50 Hz / maximum 	V	690
<ul style="list-style-type: none"> for main current circuit / at AC / at 60 Hz / maximum 	V	690
Operating current		
<ul style="list-style-type: none"> at 40 °C / rated value 	A	1 250
<ul style="list-style-type: none"> at 50 °C / rated value 	A	1 250
<ul style="list-style-type: none"> at 55 °C / rated value 	A	1 187.5
<ul style="list-style-type: none"> at 60 °C / rated value 	A	1 187.5
<ul style="list-style-type: none"> at 65 °C / rated value 	A	1 000
<ul style="list-style-type: none"> at 70 °C / rated value 	A	1 000

Auxiliary circuit

Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0

Suitability

Suitability for use		system/generator protection
----------------------------	--	-----------------------------

Adjustable parameters

Adjustable pick-up value current / of the current-dependent overload release / initial value	A	500
---	---	-----

Product details

Product component		
• Trip indicator		No
• Auxiliary switch		No
• Voltage trigger		No
• undervoltage release		No
• undervoltage release with leading contact		No
Product extension / optional / motor drive		Yes

Product function

Product function		
• of thermal overload trip unit		adjustable
• Ground fault protection		Yes
• for neutral conductors / Short-circuit and overload proof		No
• Overload protection		Yes

Short circuit

Operational short-circuit current breaking capacity (Ics)		
• at 240 V / rated value	kA	35
• at 415 V / rated value	kA	28
• at 500 V / rated value	kA	20
• at 690 V / rated value	kA	10
Maximum short-circuit current breaking capacity (Icu)		
• at 240 V / rated value	kA	65
• at 415 V / rated value	kA	55
• at 440 V / rated value	kA	35
• at 480 V / acc. to NEMA / rated value	kA	25
• at 500 V / rated value	kA	25
• at 600 V / acc. to NEMA / rated value	kA	20
• at 690 V / rated value	kA	20

Connections

Arrangement of electrical connectors / for main current circuit		front side
Type of electrical connection / for main current circuit		screw-type terminals

Mechanical Design

Height	mm	406.5
Width	mm	228.5
Depth	mm	333.5
Mounting type		fixed mounting

Environmental conditions

Ambient temperature		
----------------------------	--	--

- during operation / minimum
- during operation / maximum
- during storage / minimum
- during storage / maximum

°C	-25
°C	70
°C	-40
°C	80

Certificates

Certificate of suitability		IEC, standard switching capacity (N)
Equipment marking		
• acc. to DIN EN 61346-2		Q

General Product Approval EMC



CCC



CSA

[sonstig](#)



[TSE](#)



C-TICK

Declaration of Conformity Test Certificates Shipping Approval



EG-Konf.

[spezielle Prüfbescheinigung](#)
n



DNV



GL



RINA



RMRS

other

[sonstig](#)

[Bestätigungen](#)

[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL77121SG360AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL77121SG360AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL77121SG360AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.04.2016